

Tower Discharge System

Efficient dilution from HC to MC/LC



Tower Discharge System

Efficient dilution from HC to MC/LC

Technically proven, mechanically reliable

The Bleaching Tower Discharge System can be applied to a broad range of applications whenever pulp needs to be diluted from HC to either MC or LC.

The technology helps obtain optimum bleaching results. The design and construction contribute to a long, trouble-free life.



Available sizes

HCD30MSD	> 40 m ³	37-55 kW
HCD40MSD	> 90 m ³	55-75 kW
HCD50MSD	> 170 m ³	75-90 kW
HCD60MSD	> 300 m ³	110-132 kW
HCD70MSD	> 470 m ³	132-200 kW

Benefits

- **Two-stage dilution**
- **Excellent performance at part load**
- **Continuous and uniform pulp discharge**
- **Contributes to stable bleaching with optimum results**
- **Highly reliable with simple sealing design**



ANDRITZ AG
Graz, Austria
Phone: +43 (316) 6902-0

ANDRITZ Inc.
Muncy, USA
Phone: +1 (570) 546-8211

ANDRITZ AG
Vienna, Austria
Phone: +43 (1) 81195-0

ANDRITZ Ltd.
Montreal, Canada
Phone: +1 (514) 631-7700

www.andritz.com
mec.pulp@andritz.com