



PULP & PAPER

# SUPERIOR QUALITY CHIPS

HHQ-Chipper  
HORIZONTALLY FED CHIPPER

The HHQ-Chipper horizontally fed chipper has a unique chipping geometry that enables it to produce superior quality chips at the highest production throughput. The HHQ-Chipper with horizontal infeed is well suited for any log length from shortwood up to tree length.

The unique chipping geometry and optimized cutting speed produces thin and square shaped chips, ideal for modern cooking and/or refining process. The horizontal feeding of logs through a large spout with a controlled conveyor speed keeps the logs stable and correctly

oriented to produce superior chips. This minimizes the creation of over-size chips and ensures uniform chip sizes. Chips are gently discharged from the side of the unit to minimize the creation of pins and fines.

## ANDRTZ

ENGINEERED SUCCESS

# Chip quality with high throughput

The chipper is the most important single machine in the woodyard since chip quality is produced by the chipper. ANDRITZ produces a range of chippers including both gravity-fed and horizontally-fed units. The rugged, modular design contributes to the total economy of the ANDRITZ HHQ-Chipper horizontally fed chipper.

The direction of the chip discharge can be configured to suit different layout arrangements. A large hatch and integrated tools for knife changes assists in fast, easy, and safe maintenance.

## BENEFITS

- Superior chip quality at the highest throughputs
- Minimum fines and pins generation
- Outstanding runability
- Reliable operation and easy maintenance
- Flexibility as process needs and chip sizes change

Type	S	M	L	XL	XXL	EXL
Capacity (m <sup>3</sup> sub/h)	50 - 200	125 - 300	150 - 350	250 - 400	150 - 350	300 - 500
Chip length (mm)	14 - 34					
Disc diameter (mm)	2,328	2,758	3,046	3,360	3,360	3,870
Spout width (mm)	590	720	855	855	975	975
Number of knives	6/8/10	8/10/12	8/10/12	14/16	10/12	18/21*
Rotation speed (rpm)	348/383/421	292/316/348	265/292/316	226/249/274	249/265/292	205/220/237
Rated power (kW)	4×200	4×250	4×315	4×315	4×400	4×400
Moment of inertia (kg·m <sup>2</sup> )	3,500	8,200	13,700	21,500	22,000	41,400
Total weight w/o motor (kg)	12,500	18,500	23,500	30,500	31,000	37,500

\* 21 knives used only when the feed consists of small diameter logs



Cutaway view of the HHQ-Chipper

## EUROPE

ANDRITZ Oy  
Lahti, Finland  
p: +358 20 450 5555

## NORTH AMERICA

ANDRITZ Inc.  
Alpharetta, GA, USA  
p: +1 770 640 2500

## SOUTH AMERICA

ANDRITZ Brasil Ltda.  
Curitiba, Brazil  
p: +55 41 2103 7611

## ASIA

ANDRITZ (China) Ltd.  
Foshan, China  
p: +86 757 8296 9222

[woodprocessing@andritz.com](mailto:woodprocessing@andritz.com)

[ANDRITZ.COM](http://ANDRITZ.COM)

# ANDRITZ

All data, information, statements, photographs and graphic illustrations in this leaflet are without any obligation and raise no liabilities to or form part of any sales contracts of ANDRITZ AG or any affiliates for equipment and/or systems referred to herein. © ANDRITZ AG 2023. All rights reserved. No part of this copyrighted work may be reproduced, modified or distributed in any form or by any means, or stored in any database or retrieval system, without the prior written permission of ANDRITZ AG or its affiliates. Any such unauthorized use for any purpose is a violation of the relevant copyright laws. ANDRITZ AG, Stattegger Strasse 18, 8045 Graz, Austria. HHQ-Chipper 1.2/01.2023 EN/A4