

Second hand centrifuge **CENTRIPRESS® CP 3094**

Contact:

ANDRITZ Separation GmbH

Mr. Stefan Fielenbach

Dillenburger Straße 100

51105 Köln, Germany

Phone: +49 (221) 9856 512

Fax: +49 (221) 9856

502 stefan.fielenbach@andritz.comwww.andritz.com/separation/sh-machines**MACHINE DATA**

| | |
|----------------------------------|--------------------------------|
| Machine type | CENTRIPRESS® CP 3094 |
| Material of product wetted parts | Carbon Steel |
| Material of seals | NBR (Nitrile Butadiene Rubber) |
| Leading dimensions (L x W x H) | 6842 x 3028 x 1575 mm |
| Bowl diameter | 910 mm |
| Permissible rotational speed | 2400 rpm |
| Total Weight | 17500 kg |

EQUIPMENT AND ACCESSORIES

Feed pipe, gearbox, oil lubrication unit, vibration monitor, 2 pcs. PT100 temperature monitors, 2 pcs. Frequency inverters type ACS 600, documentation

ELECTRICAL DATA

| | |
|--------------|---------------------------------|
| Main drive | 200 kW |
| Back drive | 90 kW, with external driven fan |
| Control unit | CSC device |

PROCESS DATA

| | |
|--------------|---|
| Product feed | Depending on particle size and density e.g. ~ 60 – 100m ³ /h |
| Application | The CENTRIPRESS® system has been designed for high-dewatering of sludge: Minerals, coal sludge, tunnel sludge or sewage sludge |